SCALEMASTER®

Technical Data Sheet : Softline® Water Softeners

SL-S NON-ELECTRIC WATER SOFTENER

EAN	5027639 900292
Product Code	900292
Bathrooms/home	Up to 2
Height	492mm
Depth	425mm
Width	235mm
Flow Rate @ 1 bar Pressure Drop	30 l/min
Approximate Regeneration Time	12 min
Resin Volume	4.5 litre
Salt used per regeneration	0.27kg
Water used per regeneration	25 litre
Inlet & Outlet	3/4" BSP
Drain / Overflow	1/2" / 5/8"
Installation Kit	Not Included
Power Source	None (water pressure)
Installation Orientation	Rear
Minimum / Maximum Ambient Temp	2°C min / 23°C max
Minimum / Maximum Working Pressure	1.5 bar min / 8 bar max*
Maximum Soft Water (at 200 ppm)	689 litres
Maximum Soft Water (at 300 ppm)	443 litres
What salt to use	Block (4x4kg) or Tablet
Warranty	2 Years Parts & Labour**

*** Pressure reducing valve required above 6 bar**
**** Covers defects in materials and workmanship only**



- **Powerfully compact single-tank, non-electric water softener designed for properties with up to 2 bathrooms**
- **Compact design fits under sink**
- **Cost-effective solution with low salt consumption and no electric costs**

Installation Kits—Available Separately		
900803	900827	900810
Standard	Combi	High Flow

Technical Help - Tel: 01785 811636, Email: info@scalemaster.co.uk, Web: scalemaster.co.uk
Scalemaster® Limited - Emerald Way, Stone Business Park, Stone, Staffordshire. ST15 0SR

Issue No. 3 10/2025